

# MOBILE OIL EXTRACTION AND FILLING UNIT FOR HYDRAULIC AND LUBRICATING OILS



- clean extraction
- clean filling
- easy handling
- economical usage





Go here to the product video



# FLACOfluid PS-200

## Mobile oil extraction and filling unit

The FLACOfluid PS200 is a mobile oil device that is especially designed for the extraction and filling of e.g. hydraulic oils on production machines. With the new product generation, FLACO offers its customers a high-performance system for the handling of used and fresh oil on machines. Due to the compact dimensions, it can also be used in cramped spaces without any problems. With two large-dimensioned casters and two swivel casters, it is very manoeuvrable and easy to move. A parking brake ensures stability.



### CONVINCING TECHNOLOGY

- Vane pump with high suction and delivery rate of max. 90 l/min.
- Quick-release couplings on delivery lines for easy changeover
- Simple conversion of delivery direction via 4/2-way valve
- Wide range of additional equipment available, e.g. integrated cable drum, oil binding cloth roll.

### FLACOfluid PS-200

Due to the powerful suction pump this unit can be used conveniently to quickly extract even larger quantities of oil from storage tanks in production machines.



Picture shows full equipment



230 Volt



Fast max.  
90l/min.



200 litre tank

### TECHNICAL DATA

<b>Delivery rate</b>	Up to 90 l/min (depending on oil viscosity)
<b>Range of application</b>	Oils with a viscosity up to 100 mm <sup>2</sup> /s, with a max. temperature of 40 °C and with a flash point above 55 °C
<b>Energy supply</b>	230V 50 Hz
<b>Mains cable</b>	Schuko plug with 1.5m long supply cable Optional: 6 m cable reel
<b>Collection container</b>	200 litre plastic barrel
<b>Suction hose</b>	approx. 2 m long with quick coupling for suction lance
<b>Suction lance</b>	1×DN 26 mm, 700 mm long
<b>Chassis</b>	Powder-coated sheet steel with 2 castors and 2 swivel castors, locking brake
<b>Dimensions</b>	960 × 760 × 1.200 mm (L × B × H)
<b>Weight</b>	approx. 50 kg (empty)
<b>Ambient temperatures</b>	10 °C bis +30 °C
<b>Optional</b>	Holder for oil binding cloth roll
<b>Accessories</b>	Suction lance DN 10 mm, 700 mm long Additional suction set